

Version 9.0. Supersedes version: 8.0

Page 1 / 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

MC1 Brake Cleaner

Article number: 2897333500

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Cleaning agent

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company Normfest GmbH

Siemensstraße 23 42551 Velbert / GERMANY

Phone +49 2051 275-0 Fax +49 2051 275-141 Homepage www.normfest.com E-mail info@normfest.de

Address enquiries to

Technical information info@normfest.de

Safety Data Sheet sdb@chemiebuero.de (No dispatch of safety data sheets)

Safety data sheets are available from the supplier.

1.4 Emergency telephone number

Advisory body Call NHS 111 or a doctor

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (GB) CLP]

Aerosol 1: H222 Extremely flammable aerosol. H229 Pressurised container: May burst if

heated.

Skin Irrit. 2: H315 Causes skin irritation.

STOT SE 3: H336 May cause drowsiness or dizziness.

Aquatic Chronic 2: H411 Toxic to aquatic life with long lasting effects. Asp. Tox. 1: H304 May be fatal if swallowed and enters airways.



Version 9.0. Supersedes version: 8.0

Page 2 / 16

2.2 Label elements

The determination of properties hazardous to health does not take the propellant or carrier

material into account.

The product is required to be labelled in accordance with regulation CLP.

Hazard pictograms



Signal word DANGER

Contains: Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Hazard statements H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.

Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122°F.

P260 Do not breathe mist / vapours / spray. P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves.

P312 Call a POISON CENTER / doctor if you feel unwell.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/national regulation.

Cleaner, 648/2004/CE, contains: >=30% aliphatic hydrocarbons

2.3 Other hazards

Environmental hazards Does not contain any PBT or vPvB substances.

Other hazards Further hazards were not determined with the current level of knowledge.

SECTION 3: Composition / Information on ingredients

3.1 Substances

not applicable



Version 9.0. Supersedes version: 8.0

age 3 / 16

3.2 Mixtures

The product is a mixture.

Range [%]	Substance
30 - <50	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane
	EINECS/ELINCS: 921-024-6, Reg-No.: 01-2119475514-35-XXXX
	GHS/CLP: Flam. Liq. 2: H225 - Skin Irrit. 2: H315 - Asp. Tox. 1: H304 - STOT SE 3: H336 - Aquatic Chronic 2: H411
30 - <50	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics
	CAS: 64742-49-0, EINECS/ELINCS: 927-510-4, Reg-No.: 01-2119475515-33-XXXX
	GHS/CLP: Flam. Liq. 2: H225 - Asp. Tox. 1: H304 - Skin Irrit. 2: H315 - STOT SE 3: H336 - Aquatic Chronic 2: H411
1 - <10	Butane
	CAS: 106-97-8, EINECS/ELINCS: 203-448-7, EU-INDEX: 601-004-00-0, Reg-No.: 01-2119474691-32-XXXX
	GHS/CLP: Flam. Gas 1A: H220 - Press. Gas: H280
1 - <5	Carbon dioxide (EU occupational exposure limit value)
	CAS: 124-38-9, EINECS/ELINCS: 204-696-9
	GHS/CLP: Press. Gas: H280
1 - <5	Propane
	CAS: 74-98-6, EINECS/ELINCS: 200-827-9, EU-INDEX: 601-003-00-5, Reg-No.: 01-2119486944-21-XXXX
	GHS/CLP: Flam. Gas 1A: H220 - Press. Gas: H280

Comment on component parts

Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.

For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Change soaked clothing.

Inhalation Ensure supply of fresh air.

In the event of symptoms seek medical treatment.

Skin contact In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

Eye contact In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

Ingestion Do not induce vomiting.

In the event of symptoms seek medical treatment.

4.2 Most important symptoms and effects, both acute and delayed

Headache Drowsiness Irritant effects

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media Carbon dioxide.

Water spray jet. Dry powder. Foam.

Extinguishing media that must not

be used

Full water jet.

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products, carbon monoxide (CO), not combusted

hydrocarbons

Bursting aerosols can be forcibly projected from a fire.



Version 9.0. Supersedes version: 8.0

age 4 / 16

5.3 Advice for firefighters

Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within

the local regulations.

Cool containers at risk with water spray jet.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from all sources of ignition.

Ensure adequate ventilation.

Use personal protective equipment (protective gloves, safety glasses, protective clothing).

High risk of slipping due to leakage/spillage of product.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up mechanically.

Take up residues with absorbent material (e.g. sand, sawdust, general purpose binder,

diatomaceous earth).

Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use solvent-resistant equipment.

Use only in well-ventilated areas.

Keep away from all sources of ignition - Refrain from smoking.

Vapours can form an explosive mixture with air.

Do not eat, drink, smoke or take drugs at work.

Wash hands before breaks and after work.

Use barrier skin cream.

7.2 Conditions for safe storage, including any incompatibilities

Provide solvent-resistant and impermeable floor.

Do not store together with oxidizing agents.

Keep container in a well-ventilated place.

Protect from heat/overheating and from sun.

Keep in a cool place, heat causes increase in pressure and risk of bursting.

7.3 Specific end use(s)

See product use, SECTION 1.2



Version 9.0. Supersedes version: 8.0

Page 5 / 16

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Substance

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

EINECS/ELINCS: 921-024-6, Reg-No.: 01-2119475514-35-XXXX

Long-term exposure: 1200 mg/m³

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

CAS: 64742-49-0, EINECS/ELINCS: 927-510-4, Reg-No.: 01-2119475515-33-XXXX

Long-term exposure: 1200 mg/m³

Carbon dioxide (EU occupational exposure limit value)

CAS: 124-38-9, EINECS/ELINCS: 204-696-9

Long-term exposure: 5000 ppm, 9150 mg/m³

Short-term exposure (15-minute): 15000 ppm, 27400 mg/m³

Butane

CAS: 106-97-8, EINECS/ELINCS: 203-448-7, EU-INDEX: 601-004-00-0, Reg-No.: 01-2119474691-32-XXXX

Long-term exposure: 600 ppm, 1450 mg/m³

Short-term exposure (15-minute): 750 ppm, 1810 mg/m³

Ingredients with occupational exposure limits to be monitored (EU)

Substance / EC LIMIT VALUES

Carbon dioxide (EU occupational exposure limit value)

CAS: 124-38-9, EINECS/ELINCS: 204-696-9

Eight hours: 5000 ppm, 9000 mg/m³

DNEL

Substance

Butane, CAS: 106-97-8

There are no DNEL values established for the substance.

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Industrial, inhalative, Long-term - systemic effects, 2085 mg/m³

Industrial, dermal, Long-term - systemic effects, 300 mg/kg bw/d

general population, oral, Long-term - systemic effects, 149 mg/kg bw/d

general population, inhalative, Long-term - systemic effects, 477 mg/m³

general population, dermal, Long-term - systemic effects, 149 mg/kg bw/d

Propane, CAS: 74-98-6

There are no DNEL values established for the substance

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Industrial, inhalative, Long-term - systemic effects, 2035 mg/m³

Industrial, dermal, Long-term - systemic effects, 773 mg/kg bw/day

general population, oral, Long-term - systemic effects, 699 mg/kg bw/day

general population, dermal, Long-term - systemic effects, 699 mg/kg bw/day

general population, inhalative, Long-term - systemic effects, 608 mg/m³

PNEC

Substance

Butane, CAS: 106-97-8



Version 9.0. Supersedes version: 8.0

Page 6 / 16

There are no PNEC values established for the substance.

Propane, CAS: 74-98-6

There are no PNEC values established for the substance.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

There are no PNEC values established for the substance

8.2 Exposure controls

Additional advice on system design
Ensure adequate ventilation on workstation.

Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of

hazardous substances.

Eye protection Safety glasses. (EN 166:2001)

Hand protection >0.45 mm Nitrile rubber, >240 min (EN 374-1/-2/-3).

The details concerned are recommendations. Please contact the glove supplier for further

information.

Skin protection Protective clothing (EN 340)

Other Avoid contact with eyes and skin.

Do not inhale gases/vapours/aerosols.

Personal protective equipment should be selected specifically for the working place,

depending on concentration and quantity handled. The resistance of this equipment to

chemicals should be ascertained with the respective supplier.

Respiratory protection In the event of occupational exposure limits being exceeded or of inadequate ventilation: wear

appropriate respiratory protection.

Short term: filter apparatus, filter AX (DIN EN 14387).

Thermal hazards No information available.

Delimitation and monitoring of the

environmental exposition

See SECTION 6+7.



Version 9.0. Supersedes version: 8.0

Page 7 / 16

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid **Form** aerosol Color colourless Odor characteristic **Odour threshold** not determined pH-value not applicable pH-value [1%] not applicable Boiling point [°C] not applicable Flash point [°C] not applicable Flammability (solid, gas) [°C] not applicable Lower explosion limit not determined Upper explosion limit not determined

Oxidising properties no

Vapour pressure/gas pressure [kPa] 500 (20°C)

Density [g/cm³] 0.68987

Relative density not determined

Bulk density [kg/m³] not applicable

Solubility in water virtually insoluble

Solubility other solvents No information available.

 Partition coefficient [n-octanol/water]
 not determined

 Kinematic viscosity
 not applicable

 Relative vapour density
 not applicable

 Evaporation speed
 not applicable

 Melting point [°C]
 not applicable

Auto-ignition temperature >200

Decomposition temperature [°C] not applicable

Particle characteristics not applicable

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Evolution of flammable mixtures possible in air when heated above flash point and/or during spraying or misting. Reactions with oxidizing agents.

Because of the high vapour pressure, containers are liable to burst if temperature rises.

10.4 Conditions to avoid

Strong heating.

Safety Data Sheet (UK REACH) (GB) MC1 Brake Cleaner Article number 2897333500 Normfest GmbH 42551 Velbert



Date printed 26.01.2023, Revision 26.01.2023

Version 9.0. Supersedes version: 8.0

Page 8 / 16

10.5 Incompatible materials

Strong oxidizing agent.

10.6 Hazardous decomposition products

Flammable gases/vapours.



Version 9.0. Supersedes version: 8.0

age 9 / 16

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

Based on available data, the classification criteria are not met.

Product

ATE-mix, oral, >2000 mg/kg bw

Substance

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

LD50, oral, Rat, > 3000 mg/kg bw

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

LD50, oral, Rat, > 5840 mg/kg

Acute dermal toxicity

Based on available data, the classification criteria are not met.

Product

ATE-mix, dermal, >2000 mg/kg bw

Substance

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

LD50, dermal, Rat, > 2920 mg/kg

Acute inhalational toxicity

Based on available data, the classification criteria are not met.

Product

ATE-mix, inhalativ (mist), >20 mg/L

Substance

Butane, CAS: 106-97-8

LC50, inhalative, Rat, 658 mg/L (IUCLID)

Carbon dioxide (EU occupational exposure limit value), CAS: 124-38-9

LC0, inhalative, Human, 90000 ppm IUCLID

Propane, CAS: 74-98-6

LC50, inhalative, Rat, > 1443 mg/l (15 min) (Lit.)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

LC50, inhalative, Rat, > 25.2 mg/l (4 h)

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Substance

Butane, CAS: 106-97-8

Eye, non-irritating

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Eye, Rabbit, In vivo study, non-irritating

Propane, CAS: 74-98-6

Eye, non-irritating

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Eye, in vivo, non-irritating

Skin corrosion/irritation

Irritant

Substance



Version 9.0. Supersedes version: 8.0

Page 10 / 16

Butane, CAS: 106-97-8

dermal, non-irritating

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

dermal, Rabbit, OECD 404, irritant

Propane, CAS: 74-98-6

dermal, non-irritating

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

dermal, in vivo, irritant

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

Substance

Butane, CAS: 106-97-8

inhalative, non-sensitizing

dermal, non-sensitizing

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

No information available.

Propane, CAS: 74-98-6

inhalative, non-sensitizing

dermal, non-sensitizing

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

dermal, in vivo, non-sensitizing

Specific target organ toxicity — single exposure

Vapours may cause drowsiness and dizziness.

Substance

Butane, CAS: 106-97-8

inhalative, non-irritating

Propane, CAS: 74-98-6

inhalative, non-irritating

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

inhalative, adverse effect observed

Specific target organ toxicity — repeated exposure

Based on available data, the classification criteria are not met.

Substance

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

NOAEC, inhalative, Rat, 12470 mg/m³, Study, negativ

Propane, CAS: 74-98-6

NOAEC, inhalative, Rat, 4437 mg/m³

Mutagenicity

Does not contain a relevant substance that meets the classification criteria.

Substance

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

No information available.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

in vivo, negativ

Reproduction toxicity

Does not contain a relevant substance that meets the classification criteria.



Version 9.0. Supersedes version: 8.0

Page 11 / 16

- Fertility

Substance

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

NOAEC, inhalative, (systemic): 8117 mg/m³, The effects observed are not sufficient for classification.

- Development

Substance

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

NOAEC, inhalative, Rat, 31680 mg/m³, In vivo study, negativ

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

NOAEC, inhalative, (systemic): 8117 mg/m³, The effects observed are not sufficient for classification.

Carcinogenicity

Does not contain a relevant substance that meets the classification criteria.

Substance

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

No information available.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

no adverse effect observed

Aspiration hazard

May be fatal if swallowed and enters airways.

General remarks

Toxicological data of complete product are not available.

The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

11.2 Information on other hazards

Endocrine disrupting properties

Does not contain a relevant substance that meets the classification criteria.

Other information

SECTION 12: Ecological information

12.1 Toxicity

Substance

Butane, CAS: 106-97-8

LC50, (48h), Invertebrates, 14.22 - 69.43 mg/L

Carbon dioxide (EU occupational exposure limit value), CAS: 124-38-9

LC0, (96h), Rainbow trout, 35 mg/L (IUCLID)

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

EC50, (72h), Pseudokirchneriella subcapitata, 10 - 30 mg/l

EC50, (48h), Daphnia magna, 3 mg/l

NOEC, (21d), Daphnia magna, 0.17 mg/l

NOELR, (72h), Pseudokirchneriella subcapitata, 10 mg/l

LL50, (96h), Oncorhynchus mykiss, > 13.4 mg/l

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

LC50, (96h), Oncorhynchus mykiss, 11.4 mg/L

EC50, (48h), Daphnia magna, 3 mg/L

NOELR, (21d), Daphnia magna, 1 mg/L

NOELR, (28d), Oncorhynchus mykiss, 2.045 mg/L



Version 9.0. Supersedes version: 8.0

age 12 / 16

12.2 Persistence and degradability

Behaviour in environment

compartments

not determined

Behaviour in sewage plant

AOX-advice: No dangerous components. Contains no organic complexing agents.

Biological degradability not determined

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Endocrine disrupting properties

Does not contain a relevant substance that meets the classification criteria.

12.7 Other adverse effects

Ecological data of complete product are not available.

The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Dispose of as hazardous waste.

Waste no. (recommended) 160504* gases in pressure containers (including halons) containing dangerous substances

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

Waste no. (recommended) 150110* packaging containing residues of or contaminated by hazardous substances

150104

SECTION 14: Transport information

14.1 UN number or ID number

Transport by land according to ADR/RID

1950

Inland navigation (ADN) 1950

Marine transport in accordance with

IMDG

1950

Air transport in accordance with IATA 1950



Version 9.0. Supersedes version: 8.0

14.2 UN proper shipping name

Transport by land according to

ADR/RID

42551 Velbert

Aerosols

- Classification Code

5F

- Label

- ADR LQ

- ADR 1.1.3.6 (8.6)

Transport category (tunnel restriction code) 2 (D)

Inland navigation (ADN)

Aerosols

- Classification Code

5F

- Label



Marine transport in accordance with

IMDG

Aerosols (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane)

- EMS

F-D, S-U

- Label



- IMDG LQ

Air transport in accordance with IATA Aerosols, flammable

- Label



14.3 Transport hazard class(es)

Transport by land according to

ADR/RID

Inland navigation (ADN)

2

Marine transport in accordance with 2.1

IMDG

Air transport in accordance with IATA 2.1

14.4 Packing group

Transport by land according to

not applicable

ADR/RID

IMDG

Inland navigation (ADN) not applicable

Marine transport in accordance with

not applicable

Air transport in accordance with IATA not applicable



Version 9.0. Supersedes version: 8.0

Page 14 / 1

14.5 Environmental hazards

Transport by land according to

ADR/RID

yes

Inland navigation (ADN)

yes

Marine transport in accordance with MARINE POLLUTANT

IMDG

Air transport in accordance with IATA yes

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS 2008/98/EC 2000/532/EC); 2010/75/EU; 2004/42/EC; (EC) 648/2004; (EC) 1907/2006

(REACH); (EU) 1272/2008; 75/324/EEC ((EC) 2016/2037); (EU) 2020/878; (EU) 2016/131;

(EU) 517/2014

TRANSPORT-REGULATIONS ADR (2023); IMDG-Code (2023, 41. Amdt.); IATA-DGR (2023)

NATIONAL REGULATIONS (GB): EH40/2005 Workplace exposure limits (Second edition, published December 2011); UK

REACH; GB CLP.

- Observe employment restrictions

for people

Observe employment restrictions for young people.

- VOC (2010/75/CE) 96,6 %

665,9 g/l

15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

16.1 Hazard statements (SECTION 3)

H280 Contains gas under pressure; may explode if heated.

H220 Extremely flammable gas.

H411 Toxic to aquatic life with long lasting effects.

H336 May cause drowsiness or dizziness.

H315 Causes skin irritation.

H304 May be fatal if swallowed and enters airways.

H225 Highly flammable liquid and vapour.



Version 9.0. Supersedes version: 8.0

Page 15 / 16

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

ATE = acute toxicity estimate

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level

DNEL = Derived No Effect Level

EC50 = Median effective concentration

ECB = European Chemicals Bureau

EEC = European Economic Community

EINECS = European Inventory of Existing Commercial Chemical Substances

EL50 = Median effective loading

ELINCS = European List of Notified Chemical Substances

EmS = Emergency Schedules

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk

IC50 = Inhibition concentration, 50%

IMDG = International Maritime Code for Dangerous Goods

IUCLID = International Uniform ChemicaL Information Database

IVIS = In vitro irritation score

LC50 = Lethal concentration, 50%

LD50 = Median lethal dose

LC0 = lethal concentration, 0%

LOAEL = lowest-observed-adverse-effect level

LL50 = Median lethal loading

LQ = Limited Quantities

MARPOL = International Convention for the Prevention of Marine Pollution from Ships

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

PBT = Persistent, Bioaccumulative and Toxic substance

PNEC = Predicted No-Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

STP = Sewage Treatment Plant

TLV®/TWA = Threshold limit value - time-weighted average

TLV®STEL = Threshold limit value - short-time exposure limit

VOC = Volatile Organic Compounds

vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Aerosol 1: H222 Extremely flammable aerosol. (Bridging principle "Aerosols") H229

Pressurised container: May burst if heated. (Bridging principle "Aerosols") Skin Irrit. 2: H315 Causes skin irritation. (Calculation method)

STOT SE 3: H336 May cause drowsiness or dizziness. (Calculation method) Aquatic Chronic 2: H411 Toxic to aquatic life with long lasting effects. (Calculation method)

Asp. Tox. 1: H304 May be fatal if swallowed and enters airways. (Bridging principle "Aerosols")



Version 9.0. Supersedes version: 8.0

Page 16 / 16

Modified position

SECTION 3 been added: Butane

SECTION 3 been added: Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-

hexane

SECTION 3 deleted: Butane

SECTION 3 deleted: Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

SECTION 9 been added: not applicable

SECTION 9 been added: liquid SECTION 9 deleted: aerosol

SECTION 11 been added: Does not contain a relevant substance that meets the classification

criteria.

SECTION 12 been added: Does not contain a relevant substance that meets the classification

criteria

SECTION 12 deleted: No information available.

SECTION 16 deleted:

Copyright: Chemiebüro®



