

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Valvoline™ PETROL SYSTEM CLEANER

Version: 6.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name Valvoline™ PETROL SYSTEM CLEANER

Product code 890610

Unique Formula Identifier

(UFI)

: NRRC-MS7A-P00F-JR2Q

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Fuels and fuel additives

1.3 Details of the supplier of the safety data sheet

Company : Ellis Enterprises B.V., an affiliate of Valvoline Global

Operations

Wieldrechtseweg 39 3316 BG Dordrecht

Netherlands

Telephone +31 (0)78 654 3500 (in the Netherlands), or contact your local

CSR contact person

E-mail address of person

responsible for the SDS

SDS@valvolineglobal.com

1.4 Emergency telephone number

00-800-825-8654

, or contact your local emergency telephone number at 0 30-1 92 40

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Valvoline™ PETROL SYSTEM CLEANER

Version: 6.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

Flammable liquids, Category 2 Serious eye damage, Category 1 Specific target organ toxicity - single exposure, Category 3, Central nervous

system

Aspiration hazard, Category 1

Long-term (chronic) aquatic hazard, Category 3

H304: May be fatal if swallowed and enters airways.

H318: Causes serious eye damage.

H412: Harmful to aquatic life with long lasting

H225: Highly flammable liquid and vapour.

H336: May cause drowsiness or dizziness.

effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms









Signal word Danger

Hazard statements Highly flammable liquid and vapour. H225

> May be fatal if swallowed and enters airways. H304

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects. H412

Supplemental Hazard

Statements

EUH066

Repeated exposure may cause skin

dryness or cracking.

Precautionary statements

P101 If medical advice is needed, have product container or

label at hand.

P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eve

protection/ face protection/ hearing protection.

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P233 Keep container tightly closed.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

Valvoline_™ Global

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU)
2020/878
Valvoline™ PETROL SYSTEM CLEANER

Version: 6.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312 Call a POISON CENTER/ doctor/ .? if you feel unwell.

Storage:

P405 Store locked up.

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha propan-1-ol

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
	Index-No.		(/5 11/11/

Valvoline_™ Global

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878
Valvoline™ PETROL SYSTEM CLEANER

Version: 6.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

	Registration number		
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9 265-150-3 649-327-00-6 01-2119471843-32- xxxx	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 90 - <= 100
propan-1-ol	71-23-8 200-746-9 603-003-00-0	Flam. Liq. 2; H225 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system)	>= 20 - < 30
Hydrocarbons, C10-C13, n- alkanes, isoalkanes, cyclics, < 2% aromatics	Not Assigned 918-481-9 01-2119457273-39- xxxx	Asp. Tox. 1; H304 EUH066	>= 1 - < 10
Oxirane, ethyl-, homopolymer, monoisotridecyl ether	173140-85-7	Skin Irrit. 2; H315	>= 1 - < 10
1-Propene, 2-methyl-, homopolymer, hydroformylation products, reaction products with ammonia	337367-30-3	Skin Irrit. 2; H315 Aquatic Chronic 3; H412	>= 2,5 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses.



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ PETROL SYSTEM CLEANER

Version: 6.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

Risks : May be fatal if swallowed and enters airways.

Causes serious eye damage. May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878
Valvoline™ PETROL SYSTEM CLEANER

Version: 6.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

5.3 Advice for firefighters

Special protective equipment :

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

Valvoline, Global

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878
Valvoline™ PETROL SYSTEM CLEANER

Version: 6.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot

surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

No smoking. Keep container tightly closed in a dry and wellventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working

materials must comply with the technological safety

standards.

Storage class (TRGS 510) : 3

Further information on

storage stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878
Valvoline™ PETROL SYSTEM CLEANER

Version: 6.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9	AGW	300 mg/m3	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Group exposure limit for hydrocarbon solvent mixtures			
		MAK	50 ppm 300 mg/m3	DE DFG MAK
	Further information: Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C			
Hydrocarbons, C10-C13, n- alkanes, isoalkanes, cyclics, < 2% aromatics	918-481-9	AGW	600 mg/m3	D900LV
	Peak-limit: excursion factor (category): 2			

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Respiratory protection : No personal respiratory protective equipment normally

required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid
Colour : yellow
Odour : amine-like
Odour Threshold : No data available



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ PETROL SYSTEM CLEANER

Version: 6.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flammability : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Flash point : 18 °C

Decomposition temperature : No data available

pH : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : ca. 7 mm2/s (40 °C)

Solubility(ies)

Water solubility : No data available

No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : No data available

Relative density : No data available

Density : ca. 0,793 g/cm3 (20 °C)

Relative vapour density : No data available

Particle characteristics

Particle size : Not applicable

9.2 Other information

Oxidizing properties : No data available

Valvoline, Global

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ PETROL SYSTEM CLEANER

Version: 6.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

Self-ignition : No data available

Evaporation rate : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Avoid heat, open flame, and prolonged storage at elevated

temperatures.

10.5 Incompatible materials

Materials to avoid : Acids

Aldehydes aluminum halogens Lead peroxides

Strong oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Valvoline™ PETROL SYSTEM CLEANER

Version: 6.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

: LD50 (Rat): > 5.000 mg/kg Acute oral toxicity

Remarks: The toxicological data has been taken from

products of similar composition.

Acute inhalation toxicity LC50 (Rat): > 5.0 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute

inhalation toxicity

Remarks: The toxicological data has been taken from

products of similar composition.

Acute dermal toxicity LD50 (Rabbit): >= 3.160 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: No mortality observed at this dose.

The toxicological data has been taken from products of similar

composition.

propan-1-ol:

Acute oral toxicity LD50 (Rabbit): 2.800 mg/kg

Remarks: mortality rate

LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 33,8 mg/l

> Exposure time: 4 h Test atmosphere: vapour

Assessment: The substance or mixture has no acute

inhalation toxicity

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): 5.040 mg/kg

Acute toxicity (other routes of : LD50 (Rat): 2.164 mg/kg

administration)

Application Route: Intraperitoneal

LD50 (Mouse): 3.125 mg/kg Application Route: Intraperitoneal



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878
Valvoline™ PETROL SYSTEM CLEANER

Version: 6.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

Remarks: The toxicological data has been taken from

products of similar composition.

Acute inhalation toxicity : LD50 (Rat): > 5.000 mg/m3

Exposure time: 8 h

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): >= 3.160 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Skin corrosion/irritation

Not classified due to lack of data.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

Species : Rabbit

Assessment : Slight, transient irritation
Method : OECD Test Guideline 404

propan-1-ol:

Result : Slight, transient irritation

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Assessment : Repeated exposure may cause skin dryness or cracking.

Result : No skin irritation

Oxirane, ethyl-, homopolymer, monoisotridecyl ether:

Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Valvoline_™ Global

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ PETROL SYSTEM CLEANER

Version: 6.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system

and the skin.

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

Species : Rabbit

Method : OECD Test Guideline 405

Result : No eye irritation

Remarks : The toxicological data has been taken from products of similar

composition.

propan-1-ol:

Result : Severely irritating to eyes

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

Test Type : Maximisation Test

Species : Guinea pig

Assessment : Did not cause sensitisation on laboratory animals.

Method : OECD Test Guideline 406

Remarks : The toxicological data has been taken from products of similar

composition.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Assessment : Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Not classified due to lack of data.



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878
Valvoline™ PETROL SYSTEM CLEANER

Version: 6.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

Genotoxicity in vitro : Test Type: Ames test

Result: negative

Remarks: The toxicological data has been taken from

products of similar composition.

Germ cell mutagenicity-

Assessment

: Classified based on benzene content < 0.1% (Regulation (EC)

1272/2008, Annex VI, Part 3, Note P)

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Genotoxicity in vitro : Test Type: in vitro assay

Result: negative

Carcinogenicity

Not classified due to lack of data.

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

Carcinogenicity - : Classified based on benzene content < 0.1% (Regulation (EC)

Assessment 1272/2008, Annex VI, Part 3, Note P)

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

Assessment : May cause drowsiness or dizziness.

propan-1-ol:

Exposure routes : Inhalation

Target Organs : Central nervous system

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified due to lack of data.

Valvoline,

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878
Valvoline™ PETROL SYSTEM CLEANER

Version: 6.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

Repeated dose toxicity

Global

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Species : Rat Application Route : Oral

Method : OECD Test Guideline 422

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

May be fatal if swallowed and enters airways.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause

narcotic effects.

Solvents may degrease the skin.

SECTION 12: Ecological information

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Valvoline™ PETROL SYSTEM CLEANER

Version: 6.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

12.1 Toxicity

Components:

Naphtha (petroleum), hydrotreated heavy: Low boiling point vdrogen treated naphtha:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 - < 30 mg/l

> Exposure time: 96 h Test Type: semi-static test Test substance: WAF

Method: OECD Test Guideline 203

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 22 - < 46 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

: EL50 (Pseudokirchneriella subcapitata (green algae)): > 1.000

End point: Growth inhibition Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

Toxicity to fish (Chronic

toxicity)

NOELR: 0.182 mg/l

Exposure time: 28 d

Species: Oncorhynchus mykiss (rainbow trout)

Method: QSAR

propan-1-ol:

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)): 4.555 mg/l

Exposure time: 96 h

Test Type: flow-through test

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 3.644 mg/l

Exposure time: 48 h Test Type: static test

Toxicity to algae/aquatic

plants

: EC50 (Pseudokirchneriella subcapitata (green algae)): 9.170

mg/l

Exposure time: 48 h Test Type: static test

Toxicity to daphnia and other : EC50: > 100 mg/l

aquatic invertebrates

Exposure time: 21 d

(Chronic toxicity)

Species: Daphnia magna (Water flea)



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Valvoline™ PETROL SYSTEM CLEANER

Version: 6.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

Ш

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l

> Exposure time: 96 h Test Type: semi-static test Test substance: WAF

Method: OECD Test Guideline 203

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 1.000 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

: EL50 (Pseudokirchneriella subcapitata (green algae)): > 1.000

mq/l

Exposure time: 72 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 201

12.2 Persistence and degradability

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

Biodegradability Result: Readily biodegradable.

> Biodegradation: 89 % Exposure time: 28 d

Method: OECD Test Guideline 301F

propan-1-ol:

Biodegradability Result: Readily biodegradable.

Method: OECD Test Guideline 301D

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Biodegradability Inoculum: activated sludge

Result: Readily biodegradable.

Biodegradation: 80 % Exposure time: 28 d

Method: OECD Test Guideline 301F

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ PETROL SYSTEM CLEANER

Version: 6.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

12.3 Bioaccumulative potential

Components:

propan-1-ol:

Partition coefficient: n- : log Pow: 0,25

octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ PETROL SYSTEM CLEANER

Version: 6.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

Contaminated packaging Empty remaining contents.

> Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

Waste Code The Waste code should be assigned in discussion between

the user and the waste disposal company.

The following Waste Codes are only suggestions: 13 02 06, synthetic engine, gear and lubricating oils

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1993 **ADR** UN 1993 **RID** UN 1993 **IMDG** UN 1993 **IATA** : UN 1993

14.2 UN proper shipping name

ADN : FLAMMABLE LIQUID, N.O.S.

(NAPHTHA (PETROLEUM), HYDROTREATED HEAVY,

XYLENE)

ADR : FLAMMABLE LIQUID, N.O.S.

(NAPHTHA (PETROLEUM), HYDROTREATED HEAVY,

XYLENE)

RID : FLAMMABLE LIQUID, N.O.S.

(NAPHTHA (PETROLEUM), HYDROTREATED HEAVY,

XYLENE)

IMDG : FLAMMABLE LIQUID, N.O.S.

(NAPHTHA (PETROLEUM), HYDROTREATED HEAVY,

XYLENE)

IATA : Flammable liquid, n.o.s.

(NAPHTHA (PETROLEUM), HYDROTREATED HEAVY,

XYLENE)

14.3 Transport hazard class(es)

Valvoline_m

Global

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878
Valvoline™ PETROL SYSTEM CLEANER

Version: 6.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

		Class	Subsidiary risks
ADN	:	3	
ADR	:	3	
RID	:	3	
IMDG	:	3	
IATA	:	3	
14.4 Packing group			
ADN Packing group Classification Code Hazard Identification Number Labels	: : : : : : : : : : : : : : : : : : : :	II F1 33 3	
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	: : : : : : : : : : : : : : : : : : : :	II F1 33 3 (D/E)	
RID Packing group Classification Code Hazard Identification Number Labels	: : : : : : : : : : : : : : : : : : : :	II F1 33 3	
IMDG Packing group Labels EmS Code	: : :	II 3 F-E, <u>S-E</u>	
Packing instruction (cargo aircraft) Packing instruction (LQ)	:	364 Y341 II	
Packing group Labels	:	Flammable Liquids	
IATA_P (Passenger) Packing instruction (passenger aircraft) Packing instruction (LQ) Packing group	: : : :	353 Y341 II	
Labels	:	Flammable Liquids	

Valvoline...

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Valvoline™ PETROL SYSTEM CLEANER

Version: 6.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

14.5 Environmental hazards

Global

ADN

Environmentally hazardous no

Environmentally hazardous no

Environmentally hazardous no

Marine pollutant no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances. mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your

vendor.

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Not applicable

Not applicable

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer

Regulation (EU) 2019/1021 on persistent organic

Not applicable

pollutants (recast)

Not applicable

REACH - List of substances subject to authorisation



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ PETROL SYSTEM CLEANER

Version: 6.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

(Annex XIV)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points

Water hazard class

(Germany)

TA Luft List (Germany)

: WGK 2 obviously hazardous to water

5.2.1: Total dust: Not applicable

5.2.2: Inorganic substances in powdered form:

(a) to (d)

Not applicable

5.2.4: Inorganic substances in gaseous form:

Not applicable

5.2.5: Organic Substances:

Not applicable

5.2.7.1.1: Carcinogenic substance:

Not applicable

5.2.7.1.1: Quartz fine dust PM4:

Not applicable

5.2.7.1.1: Formaldehyde:

Not applicable 5.2.7.1.1: fibres: Not applicable

5.2.7.1.2: Germ cell mutagens:

Not applicable

5.2.7.1.3: Substances toxic to reproduction:

Not applicable

5.2.7.2: Poorly degradable, easily enrichable and highly toxic

organic substances: Not applicable



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878
Valvoline™ PETROL SYSTEM CLEANER

Version: 6.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

Regulation (EC) No. 648/2004, as amended

: 30 % and more: Aliphatic hydrocarbons

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

TCSI : Not in compliance with the inventory

TSCA : Product contains substance(s) not listed on TSCA inventory.

AIIC : Not in compliance with the inventory

DSL : This product contains the following components that are not

on the Canadian DSL nor NDSL.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2%

aromatics

Oxirane, ethyl-, homopolymer, monoisotridecyl ether 1-Propene, 2-methyl-, homopolymer, hydroformylation

products, reaction products with ammonia

Hydrocarbons, C10-C13, n-alkanes, <2% aromatics

ENCS : Not in compliance with the inventory

KECI : Not in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : Not in compliance with the inventory

NZIoC : Not in compliance with the inventory

15.2 Chemical safety assessment

No data available

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16: Other information



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ PETROL SYSTEM CLEANER

Version: 6.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H318 : Causes serious eye damage. H336 : May cause drowsiness or dizziness.

H412 : Harmful to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard
Eye Dam. : Serious eye damage
Flam. Liq. : Flammable liquids
Skin Irrit. : Skin irritation

STOT SE : Specific target organ toxicity - single exposure D900LV : Germany. TRGS 900, Limit Values in the Ambient

DE DFG MAK : Germany. MAK BAT Annex IIa

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

D900LV / AGW : Exposure limit(s):
DE DFG MAK / MAK : MAK value

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ PETROL SYSTEM CLEANER

Version: 6.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations: vPvB - Very Persistent and Very Bioaccumulative

Further information

Internal information: 000000272889

Classification of the mixture: Classification procedure:

Flam. Liq. 2	H225	Based on product data or assessment
Eye Dam. 1	H318	Calculation method
STOT SE 3	H336	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DE / EN