Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

**SAFETY DATA SHEET** 



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier
Product name
Product code
SDS #

**Product type** 

Castrol MTX Full Synthetic 75W-140 450592-DE01 450592 Liquid.

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

11 September 2023.

Date of previous issue

	Identified uses
General use of lubricants a	nd greases in vehicles or machinery-Professional
C: Consumer use PC24: Lu	bricants, greases, release products
Use of the substance/ mixture	Gear lubricant For specific application advice see appropriate Technical Data Sheet or consult our company representative.
.3 Details of the supplier o	f the safety data sheet
Supplier	Castrol Holdings Europe B.V., d'Arcyweg 76, 3198NA Europoort Rotterdam
	Castrol Germany GmbH, Überseeallee 1, 20457 Hamburg
	+49 (0) 800 863 73 70
E-mail address	MSDSadvice@bp.com
.4 Emergency telephone n	umber
EMERGENCY TELEPHONE NUMBER	Carechem: +44 (0) 1235 239 670 (24/7)
ECTION 2: Hazards	s identification
1 Classification of the sub	stance or mixture
Product definition	Mixture
Classification according to Aquatic Chronic 3, H412	Regulation (EC) No. 1272/2008 [CLP/GHS]
See Section 16 for the full te	xt of the H statements declared above.
See sections 11 and 12 for n	nore detailed information on health effects and symptoms and environmental hazards.
.2 Label elements	
Signal word	No signal word.
Hazard statements	H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements	
General	P102 - Keep out of reach of children. P101 - If medical advice is needed, have product container or label at hand.
Prevention	P273 - Avoid release to the environment.
Response	Not applicable.
Storage	Not applicable.
Disposal	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
	Not applicable.
Hazardous ingredients	Not applicable.
Hazardous ingredients Product name Castrol MTX F	

(Germany)

### **SECTION 2: Hazards identification**

Supplemental label elements	Contains Amines, C10-14-tert-alkyl. May produce an allergic reaction.
EU Regulation (EC) No. 1907/	2006 (REACH)
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Not applicable.
Special packaging requireme	<u>nts</u>
Containers to be fitted with child-resistant fastenings	Not applicable.
Tactile warning of danger	Not applicable.
2.3 Other hazards	
Results of PBT and vPvB assessment	Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	Defatting to the skin. Experimental data on one or more of the components has been used to determine all or part of the hazard classification of this product.

# **SECTION 3: Composition/information on ingredients**

3.2 Mixtures

**Product definition** 

Mixture

Poly-alpha-olefin. Ester. Proprietary performance additives.

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре	
Dec-1-ene, trimers, hydrogenated	REACH #: 01-2119486452-34 EC: 500-393-3 CAS: 157707-86-3	≥10 - ≤25	Asp. Tox. 1, H304	-	[1]	
Dec-1-ene, trimers, hydrogenated	REACH #: 01-2119493949-12 EC: 500-393-3 CAS: 157707-86-3	≥10 - ≤25	Asp. Tox. 1, H304		[1]	
tris(methylphenyl)phosphate	REACH #: 01-2119531335-46 EC: 215-548-8 CAS: 1330-78-5	≤1.2	Repr. 2, H361f Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1] [2]	
Amines, C10-14-tert-alkyl	REACH #: 01-2119456798-18 EC: 701-175-2 CAS: -	≤0.2	Acute Tox. 4, H302 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 500 mg/ kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l M [Acute] = 1 M [Chronic] = 1	[1]	
(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)- alkylamines	REACH #: 01-2119473797-19 EC: 627-034-4 CAS: 1213789-63-9	≤0.1	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 500 mg/ kg M [Acute] = 10 M [Chronic] = 10	[1]	

#### See Section 16 for the full text of the H statements declared above.

Туре

[1] Substance classified with a health or environmental hazard [2] Substance with a workplace exposure limit

 Product name
 Castrol MTX Full Synthetic 75W-140
 Product code
 450592-DE01
 Page: 2/15

 Version 15
 Date of issue 26 June 2024
 Format
 Germany
 Language
 ENGLISH

 Date of previous issue
 11 September 2023.
 (Germany)
 Comparison of the second sec

# **SECTION 3: Composition/information on ingredients**

Occupational exposure limits, if available, are listed in Section 8.

#### **SECTION 4: First aid measures**

4.1 Description of first aid me	asures
Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if symptoms occur.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### 4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Potential acute health effect	<u>xts</u>
Inhalation	Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.
Ingestion	No known significant effects or critical hazards.
Skin contact	Defatting to the skin. May cause skin dryness and irritation.Product not classified for sensitisation. Based on data available for this or related materials.
Eye contact	No known significant effects or critical hazards.
Delayed and immediate effe	ects as well as chronic effects from short and long-term exposure
Inhalation	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects.						
SECTION 5: Firefighting	SECTION 5: Firefighting measures						
5.1 Extinguishing media							
Suitable extinguishing media	Use foam or all-purpose dry chemical to extinguish.						
Unsuitable extinguishing media	Do not use water jet. The use of a water jet may cause the fire to spread by splashing the burning product.						
5.2 Special hazards arising fro	m the substance or mixture						
Hazards from the substance or mixture	In a fire or if heated, a pressure increase will occur and the container may burst.						
Hazardous combustion products	Combustion products may include the following: carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide) phosphorus oxides						
5.3 Advice for firefighters							
Special precautions for fire-fighters	No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. This material is harmful to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.						
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.						

Product name Castrol MTX Full Synthetic 75W-140			Product code 450592-DE01			Page: 3/15	
Version 15	Date of issue	26 June 2024	Format	Germany		Language	ENGLISH
Date of previo	ous issue	11 September 2023.		(Germany)			

# **SECTION 6: Accidental release measures**

6.1 Personal precautions, prot	ective equipment and emergency procedures
For non-emergency personnel	Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment.
For emergency responders	Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and material for c	containment and cleaning up
Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	See Section 1 for emergency contact information. See Section 5 for firefighting measures. See Section 8 for information on appropriate personal protective equipment. See Section 12 for environmental precautions. See Section 13 for additional waste treatment information.

# **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe hand	dling
Protective measures	Put on appropriate personal protective equipment. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid contact of spilt material and runoff with soil and surface waterways. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Empty containers retain product residue and can be hazardous.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/ containers designed for use with this product. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.
Not suitable	Prolonged exposure to elevated temperature
Germany - Storage code	10
7.3 Specific end use(s)	
Recommendations	See section 1.2 and Exposure scenarios in annex, if applicable.

ſ	Product name Castrol MTX Full Synthetic 75W-140			Product code 450592-DE01			Page: 4/15	
	Version 15	Date of issue	26 June 2024	Format	Germany		Language	ENGLISH
	Date of previo	ous issue	11 September 2023.		(Germany)			

#### **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 8.1 Control parameters

Occupational exposure limits					
Product/ingredie	nt name Exposure limit values				
kris(methylphenyl)phosphate	<b>TRGS 900 OEL (Germany). [Tritolylphosphat] Absorbed through skin.</b> PEAK: 10 mg/m <sup>3</sup> 15 minutes. Issued/Revised: 3/2021 Form: Inhalable fraction TWA: 5 mg/m <sup>3</sup> 8 hours. Issued/Revised: 3/2021 Form: Inhalable fraction				
Recommended monitoring procedures	Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - Guide for the performance of procedures for the assessment of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.				
Biological exposure indices					

Product/ingredient name

**Exposure indices** 

## No exposure indices known.

#### Derived No Effect Level

Product/ingredient name	Туре	E	xposure	Value	Population	Effects
Amines, C12-14-tert-alkyl	DNEL	Long term Inhalation	-	12.5 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	-	12.1 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Inhalation	-	2.5 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	-	1.2 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Oral	-	0.35 mg/kg bw/ day	General population	Systemic

#### Predicted No Effect Concentration

- -

Product/ingredient name	Compartment Detail	Value	Method Detail
mines, C12-14-tert-alkyl	Fresh water	0.001 mg/l	-
	Sewage Treatment Plant	0.635 mg/l	-
	Fresh water sediment	2.14 mg/kg	-
	Marine water sediment	0.214 mg/kg	-
	Soil	0.428 mg/kg	-
	Secondary Poisoning	4.71 mg/kg	-

8.2 Exposure controls	
Appropriate engineering controls	<ul> <li>Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.</li> <li>All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.</li> <li>Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.</li> </ul>
Individual protection measu	<u>ires</u>
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.
Respiratory protection	

Product name	Castrol MTX Fu	III Synthetic 75W-140		Product code 4	50592-DE01	Page: 5/15
Version 15	Date of issue	26 June 2024	Format	Germany	Language	ENGLISH
Date of previo	ous issue	11 September 2023.		(Germany)		

# SECTION 8: Exposure controls/personal protection

	In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.
Eye/face protection	Safety glasses with side shields.
Skin protection	
Hand protection	General Information:
	Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).
	Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.
	Recommended: Nitrile gloves. Breakthrough time:
	Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type. Our recommendations on the selection of gloves are as follows:
	Continuous contact:
	Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained. If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.
	Short-term / splash protection:
	Recommended breakthrough times as above. It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.
	Glove Thickness:
	For general applications, we recommend gloves with a thickness typically greater than 0.35 mm
	It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.
	Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:
	• Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
	• Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

# SECTION 8: Exposure controls/personal protection

Skin and body	Use of protective clothing is good industrial practice.
	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
	Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.
<u>Refer to standards:</u>	Respiratory protection: EN 529 Gloves: EN 420, EN 374 Eye protection: EN 166 Filtering half-mask: EN 149 Filtering half-mask with valve: EN 405 Half-mask: EN 140 plus filter Full-face mask: EN 136 plus filter Particulate filters: EN 143 Gas/combined filters: EN 14387
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

## 9.1 Information on basic physical and chemical properties

9.1 Information on basic physical a	and chemical properties				
Physical state	Liquid.				
Colour	Amber.				
Odour	Not available.				
Odour threshold	Not available.				
Melting point/freezing point	Not available.				
Initial boiling point and boiling range	Not available.				
Flammability	Not available.				
Lower and upper explosion limit	Not available.				
Flash point	Open cup: >180°C (>356	°F) [Cleveland]			
Auto-ignition temperature	Ingredient name	°C	°F	Method	
	▶ C-1-ene, homopolymer, hydrogenated Dec-1-ene, oligo hydrogenated	343 to 369 omers,	649.4 to 696.2	ASTM D 2159	
	Dec-1-ene, homopolymer, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159	
	Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligo hydrogenated	343 to 369 omers,	649.4 to 696.2	ASTM D 2159	
Decomposition temperature	Not available.				
рН	Not available.				
Kinematic viscosity	Kinematic: 182 mm <sup>2</sup> /s (18 Kinematic: 24.5 to 25.5 n		5.5 cSt) at 100°	С	
Solubility					
	Media	Result			
	water	Not soluble			
Partition coefficient n-octanol/ water (log value)	Not applicable.				
Vapour pressure	✓0.01 kPa				
Density and/or Relative density	<1000 kg/m³ (<1 g/cm³) a	at 15°C			
Relative vapour density	Not available.				
Particle characteristics					
Median particle size	Not applicable.				
9.2 Other information					
Product name Castrol MTX Full Synt	thetic 75W-140		Product code	450592-DE01	Page: 7/15
Version 15 Date of issue 26 Ju	ne 2024	Format	Germany	Language	ENGLISH
Date of previous issue 11 Se	eptember 2023.		(Germany)		

# **SECTION 9: Physical and chemical properties**

•=•····	· · · · · · · · · · · · · · · · · · ·	
Evaporation rate	Not available.	
Explosive properties	Not available.	
Oxidising properties	Not available.	
Pour point	-54 °C	

# **SECTION 10: Stability and reactivity**

	-
10.1 Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
10.2 Chemical stability	The product is stable.
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
10.4 Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
10.5 Incompatible materials	Reactive or incompatible with the following materials: oxidising materials.
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity estimates	Acute to	oxicitv e	stimates
--------------------------	----------	-----------	----------

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Zastrol MTX Full Synthetic 75W-140	N/A	154201.7	N/A	257.0	N/A
Amines, C12-14-tert-alkyl	500	300	N/A	0.5	N/A
(Z)-octadec-9-enylamine	500	N/A	N/A	N/A	N/A

#### Aspiration hazard

Product/ingredient name		Result		
Sec-1-ene, homopolymer, hydrogenated		ASPIRATION HAZARD - Category 1		
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated		ASPIRATION HAZARD - Category 1		
(Z)-octadec-9-enylamine		ASPIRATION HAZARD - Category 1		
Conclusion/Summary	Not classified. Based on av	ailable data, the classification criteria are not met.		
Information on likely routes of exposure	Routes of entry anticipated:	Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.		
Potential acute health effect	<u>ets</u>			
Inhalation	Vapour inhalation under aml pressure.	Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.		
Ingestion	No known significant effects	No known significant effects or critical hazards.		
Skin contact		Defatting to the skin. May cause skin dryness and irritation.Product not classified for sensitisation. Based on data available for this or related materials.		
Eye contact	No known significant effects or critical hazards.			
Symptoms related to the pl	hysical, chemical and toxicolog	ical characteristics		
Inhalation	May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.			
Ingestion	No specific data.			
Skin contact	Adverse symptoms may include the following: irritation dryness cracking			
Eye contact	No specific data.			

Product name (	Castrol MTX Fu	III Synthetic 75W-140		Product code 45	50592-D	E01	Page: 8/15
Version 15	Date of issue	26 June 2024	Format	Germany		Language	ENGLISH
Date of previo	us issue	11 September 2023.		(Germany)			

#### **SECTION 11: Toxicological information**

Inhalation	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.
Potential chronic health eff	fects
General	No known significant effects or critical hazards.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
<b>Developmental effects</b>	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.

#### 11.2 Information on other hazards

11.2.1 Endocrine disrupting prop	perties
Not available.	
Remarks -Endocrine disrupting properties for human health Conclusion/ Summary 11.2.2 Other information Not available	Not available.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Environmental hazards Harmful to aquatic life with long lasting effects.

#### 12.2 Persistence and degradability

Not expected to be rapidly degradable.

#### **12.3 Bioaccumulative potential**

This product is not expected to bioaccumulate through food chains in the environment.

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	Not available.
Mobility	Spillages may penetrate the soil causing ground water contamination.

#### 12.5 Results of PBT and vPvB assessment

Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.

12.6 Endocrine disrupting properties	Not available.
Remarks - Endocrine disrupting properties for environment Conclusion/ Summary	Not available.
Other ecological information	Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.
12.7 Other adverse effects	No known significant effects or critical hazards.

#### **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

Product					
Methods of disposal	Where possible, arrange for product licensed waste disposal contractor ir		,		d person/
Hazardous waste	Yes.				
<u>European waste catalogue (</u>	(EWC)				
Product name Castrol MTX Full	Synthetic 75W-140		Product code 450592	2-DE01	Page: 9/15
Version 15 Date of issue 2	26 June 2024	Format	Germany	Language	ENGLISH
Date of previous issue	11 September 2023.		(Germany)		

#### **SECTION 13: Disposal considerations**

Waste code	Waste designation				
13 02 06*	13 02 06* synthetic engine, gear and lubricating oils				
However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative wa disposal code to be assigned by the end user.					
Packaging					
Methods of disposal	Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.				

	licensed waste disposal contractor in accordance with local regulations.
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Empty containers represent a fire hazard as they may contain flammable product residues and vapour. Never weld, solder or braze empty containers. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
References	Commission 2014/955/EU Directive 2008/98/EC

## **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

14.6 Special precautions for Not available. user

 
 14.7 Maritime transport in bulk according to IMO instruments
 Not available.

#### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

# Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
Sastrol Transmax Axle Long Life 75W-140 (Neuhof) Parent	95-100	3

#### Labelling

Not applicable.

```
Other regulations
REACH Status
```

The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

Product name	Castrol MTX Full Synthetic 75W-140		Product code 450592	DE01	Page: 10/15
Version 15	Date of issue 26 June 2024 Fo	ormat	Germany	Language	ENGLISH
Date of previo	us issue 11 September 2023.		(Germany)		

# SECTION 15: Regulatory information

SECTION 15: Regulate	by mornation				
United States inventory (TSCA 8b)	All components are active or exempted.				
Australia inventory (AIIC)	All components are listed or exempted.				
Canada inventory	Il components are listed or exempted.				
China inventory (IECSC)	Il components are listed or exempted.				
Japan inventory (CSCL)	All components are listed or exempted.				
Korea inventory (KECI)	All components are listed or exempted.				
Philippines inventory (PICCS)	All components are listed or exempted.				
Taiwan Chemical Substances Inventory (TCSI)	All components are listed or exempted.				
Explosive precursors	Not applicable.				
Ozone depleting substances	<u>(1005/2009/EU)</u>				
Not listed.					
Prior Informed Consent (PIC Not listed.	) (649/2012/EU)				
Persistent Organic Pollutant Not listed.	Persistent Organic Pollutants Not listed.				
EU - Water framework direct	ive - Priority substances				
None of the components are lis	sted.				
Seveso Directive					
This product is not controlled un	der the Seveso Directive.				
National regulations					
Hazardous incident ordinance	ee				
This product is not controlled u	nder the Germany Hazardous Incident Ordinance.				
Hazard class for water	2 (classified according AwSV)				
Prohibited Chemicals Regulation (ChemVerbotsV)When placed on the market in Germany, this product is not subject to the Prohibited Chemical Regulation (ChemVerbotsV).					
Occupational restrictions	Observe employment restrictions in the following: Gesetz zum Schutz der arbeitenden Jugend (Jugendarbeitsschutzgesetz – JArbSchG) Gesetz zum Schutz von Müttern bei der Arbeit, in der Ausbildung und im Studium (Mutterschutzgesetz – MuSchG)				
15.2 Chemical safety assessment	A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture. A Chemical Safety Assessment has not been carried out for the mixture itself.				

# **SECTION 16: Other information**

Abbreviations and acronyms	ADN = European Provisions concern Inland Waterway	ng the International Ca	arriage of Dangerou	is Goods by	
	ADR = The European Agreement cor Road	cerning the Internatior	al Carriage of Dan	gerous Goods by	
	ATE = Acute Toxicity Estimate				
	BCF = Bioconcentration Factor				
	CAS = Chemical Abstracts Service				
	CLP = Classification, Labelling and P	ackaging Regulation [F	Regulation (EC) No	. 1272/2008]	
	CSA = Chemical Safety Assessment				
	CSR = Chemical Safety Report				
	DMEL = Derived Minimal Effect Level				
	DNEL = Derived No Effect Level				
	EINECS = European Inventory of Exi	sting Commercial chen	nical Substances		
	ES = Exposure Scenario				
	EUH statement = CLP-specific Hazar	d statement			
	EWC = European Waste Catalogue				
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals				
	IATA = International Air Transport As	sociation			
	IBC = Intermediate Bulk Container				
	IMDG = International Maritime Dange	rous Goods			
	LogPow = logarithm of the octanol/wa	ter partition coefficient			
Product name Castrol MTX Full	Synthetic 75W-140	Product code	450592-DE01	Page: 11/15	

Flouuct hame		iii Synthetic 7500-140		FIGUACE COUR 450592-	DEUT	Fage. 11/15
Version 15	Date of issue	26 June 2024	Format	Germany	Language	ENGLISH
Date of previo	ous issue	11 September 2023.		(Germany)		

#### **SECTION 16: Other information**

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) OECD = Organisation for Economic Co-operation and Development PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006] RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail RRN = REACH Registration Number SADT = Self-Accelerating Decomposition Temperature SVHC = Substances of Very High Concern STOT-RE = Specific Target Organ Toxicity - Repeated Exposure STOT-SE = Specific Target Organ Toxicity - Single Exposure TWA = Time weighted average UN = United Nations UVCB = Complex hydrocarbon substance VOC = Volatile Organic Compound vPvB = Very Persistent and Very Bioaccumulative Varies = may contain one or more of the following 64741-88-4 / RRN 01-2119488706-23, 64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN 01-2119487081-40, 64741-96-4/ RRN 01-2119483621-38, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN 01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN 01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN 01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN 01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8, 64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42, 72623-85-9 / RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 / RRN 01-2119474889-13

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classif	ication	Justification
Aquatic Chronic 3, H412		Calculation method
Full text of abbreviated H statements	H302 H304 H311 H314 H317 H318 H330 H335 H361f H373 H400 H410	Harmful if swallowed. May be fatal if swallowed and enters airways. Toxic in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Fatal if inhaled. May cause respiratory irritation. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.
Full text of classifications [CLP/GHS]	Acute Tox. 2 Acute Tox. 3 Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Asp. Tox. 1 Eye Dam. 1 Repr. 2 Skin Corr. 1B Skin Sens. 1A STOT RE 2 STOT SE 3	ACUTE TOXICITY - Category 2 ACUTE TOXICITY - Category 3 ACUTE TOXICITY - Category 4 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 ASPIRATION HAZARD - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 REPRODUCTIVE TOXICITY - Category 2 SKIN CORROSION/IRRITATION - Category 1B SKIN SENSITISATION - Category 1A SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
<u>History</u>		
Date of issue/ Date of revision	26/06/2024.	
Date of previous issue	11/09/2023.	
Prepared by	Product Stewardship	
Indicates information that	has changed from previou	usly issued version.
Notice to reader		

ſ	Product name	Castrol MTX Fu	II Synthetic 75W-140		Product code 45059	2-DE01	Page: 12/15
	Version 15	Date of issue	26 June 2024	Format	Germany	Language	ENGLISH
	Date of previo	ous issue	11 September 2023.		(Germany)		

#### **SECTION 16: Other information**

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name Castrol MTX F	ull Synthetic 75W-140		Product code 4	50592-DE01	Page: 13/15
Version 15 Date of issue	26 June 2024	Format	Germany	Language	ENGLISH
Date of previous issue	11 September 2023.		(Germany)		



# Annex to the extended Safety Data Sheet (eSDS)

Professional

Identification of the subst	ance or mixture
Product definition	Mixture
Code	450592-DE01
Product name	Castrol MTX Full Synthetic 75W-140
Section 1: Title	
Short title of the exposure scenario	General use of lubricants and greases in vehicles or machinery - Professional
List of use descriptors	Identified use name: General use of lubricants and greases in vehicles or machinery-Professional
	Process Category: PROC01, PROC02, PROC08a, PROC08b, PROC20 Sector of end use: SU22
	Subsequent service life relevant for that use: No.
	Environmental Release Category: ERC09a, ERC09b Specific Environmental Release Category: ATIEL-ATC SPERC 9.Bp.v1
Processes and activities covered by the exposure scenario	Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

#### Section 2 Operational conditions and risk management measures

Section 2.1 Control of worker exposure No exposure scenario is presented because the product is not classified for Human Health Contributing scenarios: Operational conditions and risk management measures

	14/15
Castrol MTX Full Synthetic 75W-140	General use of lubricants and greases in vehicles or machinery - Professional
Technical conditions and measures at process level (source) to prevent release:	Common practices vary across sites thus conservative process release estimates used.
Release fraction to wastewater from proces (after typical onsite RMMs and before sewage treatment plan)	s 6.25E-4
Release fraction to soil from process (after typical onsite RMMs)	1E-03
Release fraction to air (after typical onsite RMMs)	1.00E-04
Other conditions affecting environmental exposure:	Negligible wastewater emissions as process operates without water contact.
Local marine water dilution factor	100
Local freshwater dilution factor	10
Environment factors not influenced by risk management:	
Emission days	365
Frequency and duration of use:	
EU tonnage of risk determining substance per year:	5.39 Tonnes/year
Amounts used:	
Section 2.2: Control of environmental ex	posure

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:	Prevent discharge of undissolved substance to or recover from onsite wastewater. User sites are assumed to be provided with oil/water separators and waste water to be discharged via a sewage treatment plant
Organisational measures to prevent/limit release from site:	Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.
Conditions and measures related to sewage treatment plant:	
Estimated substance removal from wastewater via on-site sewage treatment	79
Assumed domestic sewage treatment plant flow rate (m3/d)	2.00E+3
Maximum allowable site tonnage (M <sub>Safe</sub> ) based on release following total wastewater treatment removal as product:	161.6
Conditions and measures related to external treatment of waste for disposal:	External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external	External recovery and recycling of waste should comply with

#### Section 3: Exposure estimation and reference to its source

Exposure estimation and reference to its s	ource - Environment
Exposure assessment (environment):	Used ECETOC TRA model (May 2010 release).
Exposure estimation and reference to its s	ource - Workers

#### Section 4: Guidance to check compliance with the exposure scenario

Environment	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.ATIEL.org/REACH_GES
Health	No exposure scenario is presented because the product is not classified for Human Health