

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name Valvoline™ INDUSTRIAL CLEANER

Product code 887068

Unique Formula Identifier

(UFI)

: JW3Y-WJNG-3T4J-AP6J

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Cleaner.

1.3 Details of the supplier of the safety data sheet

Company : Ellis Enterprises B.V., an affiliate of Valvoline Global

**Operations** 

Wieldrechtseweg 39 3316 BG Dordrecht

Netherlands

Telephone +31 (0)78 654 3500 (in the Netherlands), or contact your local

CSR contact person

E-mail address of person

responsible for the SDS

SDS@valvolineglobal.com

### 1.4 Emergency telephone number

00-800-825-8654

, or contact your local emergency telephone number at 0 30-1 92 40

# **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

# **SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single H336: May cause drowsiness or dizziness. exposure, Category 3, Central nervous

Long-term (chronic) aquatic hazard, H411: Toxic to aquatic life with long lasting effects.

Category 2

#### 2.2 Label elements

system

# Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :







Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : P101 If medical advice is needed, have product container or

label at hand.

P102 Keep out of reach of children.

## Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

# Response:

P391 Collect spillage.

#### Storage:

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

# Disposal:

P501 Dispose of contents/ container to an approved waste

# Valvoline, Global

### SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

disposal plant.

# Hazardous components which must be listed on the label:

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha acetone

1-methoxy-2-propanol

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

# Components

| Chemical name   | CAS-No. EC-No. Index-No. Registration number                         | Classification   | Concentration<br>(% w/w) |
|---|--|--|--------------------------|
| Naphtha (petroleum),<br>hydrotreated light; Low boiling<br>point hydrogen treated naphtha | 64742-49-0<br>265-151-9<br>649-328-00-1<br>01-2119475514-35-<br>xxxx | Flam. Liq. 2; H225<br>Skin Irrit. 2; H315<br>STOT SE 3; H336<br>(Central nervous<br>system)<br>Asp. Tox. 1; H304<br>Aquatic Chronic 2;<br>H411 | >= 70 - < 80             |
| acetone   | 67-64-1<br>200-662-2<br>606-001-00-8<br>01-2119471330-49-<br>xxxx    | Flam. Liq. 2; H225<br>Eye Irrit. 2; H319<br>STOT SE 3; H336<br>(Central nervous<br>system)<br>EUH066   | >= 40 - < 50             |



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

| 1-methoxy-2-propanol              | 107-98-2<br>203-539-1<br>603-064-00-3<br>01-2119457435-35-<br>xxxx | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>(Central nervous<br>system) | >= 5 - < 10 |
|-----------------------------------|--|--|-------------|
| Substances with a workplace expos | sure limit :   |  |             |
| carbon dioxide                    | 124-38-9<br>204-696-9  | Press. Gas Liquefied gas; H280                                       | >= 5 - < 10 |

For explanation of abbreviations see section 16.

## **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

Risks : Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

# Valvoline, Global

# **SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

Treat symptomatically.

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

No hazardous combustion products are known

# 5.3 Advice for firefighters

Special protective equipment :

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

# Valvoline, Global

### SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

# **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

# 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, soak up with non-combustible absorbent

material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local /

national regulations (see section 13).

Ensure adequate ventilation.

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

# **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Container may be opened only under exhaust ventilation

hood.

Open drum carefully as content may be under pressure.

Dispose of rinse water in accordance with local and national

# Valvoline, Global

### SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

regulations.

Advice on protection against

fire and explosion

Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

# 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Storage class (TRGS 510) : 2B

Further information on

storage stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

# **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

# **Occupational Exposure Limits**

| Components | CAS-No.   | Value type (Form of exposure) | Control parameters | Basis      |
|------------|---|-------------------------------|--------------------|------------|
| acetone    | 67-64-1   | TWA                           | 500 ppm            | 2000/39/EC |
|            |   |                               | 1.210 mg/m3        |            |
|            | Further information: Indicative   |                               |                    |            |
|            |   | AGW                           | 500 ppm            | DE TRGS    |
|            |   |                               | 1.200 mg/m3        | 900        |
|            | Peak-limit: excursion factor (category): 2;(I)                            |                               |                    |            |
|            | Further information: When there is compliance with the OEL and biological |                               |                    |            |

# Valvoline<sub>™</sub> Global

# **SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

|                | tolerance val   | ues, there is no risk   | of harming the unborn child |                |
|----------------|---|---|-----------------------------|----------------|
|                |   | MAK   | 500 ppm                     | DE DFG MAK     |
|                |   |   | 1.200 mg/m3                 |                |
|                | Peak-limit: ex  | Peak-limit: excursion factor (category): 2; I Further information: According to currently available information damage to the embryo or foetus cannot be excluded after exposure to concentrations at |                             |                |
|                |   |   |                             |                |
|                |   |   |                             |                |
|                | the level of the MAK and BAT values   |   |                             | _              |
| carbon dioxide | 124-38-9  | TWA   | 5.000 ppm                   | 2006/15/EC     |
|                |   |   | 9.000 mg/m3                 |                |
|                | Further infor   | mation: Indicative  |                             |                |
| 1              |   | AGW   | 5.000 ppm                   | DE TRGS        |
|                |   |   | 9.100 mg/m3                 | 900            |
|                | Peak-limit: excursion factor (category): 2;(II)                                   |   |                             |                |
|                |   | MAK   | 5.000 ppm                   | DE DFG MAK     |
|                |   |   | 9.100 mg/m3                 |                |
|                | Peak-limit: ex  | xcursion factor (cate   | gory): 2; II                | •              |
| 1-methoxy-2-   | 107-98-2  | TWA   | 100 ppm                     | 2000/39/EC     |
| propanol       |   |   | 375 mg/m3                   |                |
|                | Further information: Identifies the possibility of significant uptake thr         |   |                             | ke through the |
|                | skin, Indicati  | skin, Indicative  |                             |                |
|                |   | STEL  | 150 ppm                     | 2000/39/EC     |
|                |   |   | 568 mg/m3                   |                |
|                | Further information: Identifies the possibility of significant uptake through the |   |                             |                |
|                | skin, Indicati  | ve  |                             | _              |
|                |   | AGW   | 100 ppm                     | DE TRGS        |
|                |   |   | 370 mg/m3                   | 900            |
|                | Peak-limit: excursion factor (category): 2;(I)                                    |   |                             |                |
|                | Further information: When there is compliance with the OEL and biological         |   |                             |                |
|                | tolerance values, there is no risk of harming the unborn child                    |   |                             | J              |
|                |   | MAK   | 100 ppm                     | DE DFG MAK     |
|                |   |   | 370 mg/m3                   |                |
|                | Further information: Damage to the embryo or foetus is unlikely when the          |   |                             |                |
|                | MAK value or the BAT value is observed  |   |                             | -              |

# **Biological occupational exposure limits**

| Substance name       | CAS-No.  | Control parameters                           | Sampling time                                       | Basis         |
|----------------------|----------|--|---|---------------|
| acetone              | 67-64-1  | Acetone: 50 mg/l<br>(Urine)                  | Immediately after exposure or after working hours   | TRGS 903      |
|                      |          | Acetone: 50 mg/l<br>(Urine)                  | Immediately after exposition or after working hours | DE DFG<br>BAT |
| 1-methoxy-2-propanol | 107-98-2 | 1-Methoxypropan-<br>2-ol: 15 mg/l<br>(Urine) | Immediately after exposure or after working hours   | TRGS 903      |

### SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

|  | 1-<br>methoxypropanol-<br>2: 15 mg/l<br>(Urine) | Immediately after exposition or after working hours | DE DFG<br>BAT |
|--|---|---|---------------|
|--|---|---|---------------|

### 8.2 Exposure controls

# Personal protective equipment

Eye/face protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Equipment should conform to EN 143

Filter type : Particulates type (P)

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Physical state : aerosol
Colour : clear
Odour : solvent-like
Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling :

range

Not applicable

Flammability : No data available

Upper explosion limit / Upper

flammability limit

13 %(V)

Lower explosion limit / Lower

flammability limit

0,6 %(V)

Flash point : Not applicable



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

Ignition temperature : > 200 °C

Decomposition temperature : No data available

pH : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : 247 hPa (20 °C)

Relative density : No data available

Density : 0,71 g/cm3 (20 °C)

Relative vapour density : No data available

Particle characteristics

Particle size : Not applicable

9.2 Other information

Oxidizing properties : No data available

Self-ignition : not auto-flammable

Evaporation rate : No data available

# **SECTION 10: Stability and reactivity**

# 10.1 Reactivity

No decomposition if stored and applied as directed.



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

# 10.2 Chemical stability

No decomposition if stored and applied as directed.

# 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Exposure to air or moisture over prolonged periods.

10.5 Incompatible materials

Materials to avoid : Acids

alkalis
aluminum
Amines
Ammonia
halogens
peroxides
Reducing agents
salts of strong bases

strong bases

Strong oxidizing agents

# 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

# **SECTION 11: Toxicological information**

# 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

# **Acute toxicity**

Not classified based on available information.

#### **Components:**

## Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:

Acute oral toxicity : LD50 (Rat): > 5.840 mg/kg

Remarks: The toxicological data has been taken from

products of similar composition.

Acute inhalation toxicity : LC50 (Rat): > 25,2 mg/l

Exposure time: 4 h

# Valvoline<sub>™</sub> Global

# **SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2.800 - 3.100 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: The toxicological data has been taken from

products of similar composition.

acetone:

Acute oral toxicity : LD50 (Rat, female): 5.800 mg/kg

Acute inhalation toxicity : LC50 (Rat, female): 76 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 7.426 mg/kg

1-methoxy-2-propanol:

Acute oral toxicity : LD50 (Rat): 4.016 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 10000 ppm

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 13.000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

**Product:** 

Remarks : May cause skin irritation in susceptible persons.

**Components:** 

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:

Result : Irritating to skin.

acetone:

Result : Slight, transient irritation

Result : Repeated exposure may cause skin dryness or cracking.

1-methoxy-2-propanol:

# **SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

Assessment : No skin irritation Result : No skin irritation

carbon dioxide:

Assessment : No skin irritation
Result : No skin irritation

# Serious eye damage/eye irritation

Causes serious eye irritation.

**Product:** 

Remarks : May cause irreversible eye damage.

# **Components:**

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:

Result : Slight, transient irritation

acetone:

Assessment : Irritating to eyes. Result : Irritating to eyes.

1-methoxy-2-propanol:

Assessment : Slight, transient irritation Result : Slight, transient irritation

carbon dioxide:

Result : No eye irritation

# Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

# Respiratory sensitisation

Not classified based on available information.

#### **Components:**

# 1-methoxy-2-propanol:

Assessment : Did not cause sensitisation on laboratory animals.



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

# Germ cell mutagenicity

Not classified based on available information.

# **Components:**

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:

Germ cell mutagenicity: Classified based on benzene content < 0.1% (Regulation (EC)

Assessment 1272/2008, Annex VI, Part 3, Note P)

1-methoxy-2-propanol:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Result: negative

Carcinogenicity

Not classified based on available information.

**Components:** 

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:

Carcinogenicity - : Classified based on benzene content < 0.1% (Regulation (EC)

Assessment 1272/2008, Annex VI, Part 3, Note P)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

**Components:** 

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:

Assessment : May cause drowsiness or dizziness.

acetone:

Exposure routes : Inhalation
Target Organs : Nervous system

Assessment : May cause drowsiness or dizziness.

1-methoxy-2-propanol:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

# **Aspiration toxicity**

Not classified based on available information.

# **Components:**

# Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:

May be fatal if swallowed and enters airways.

#### acetone:

May be harmful if swallowed and enters airways.

#### 11.2 Information on other hazards

# **Endocrine disrupting properties**

# **Product:**

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### **Further information**

**Product:** 

Remarks : Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause

narcotic effects.

Solvents may degrease the skin.

# **SECTION 12: Ecological information**

## 12.1 Toxicity

### **Components:**

# Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 11,4 mg/l

Exposure time: 96 h
Test Type: semi-static test
Test substance: WAF

### SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia hyalina (water flea)): 3 mg/l

Exposure time: 48 h
Test Type: static test
Test substance: WAF

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): > 10 -

30 mg/l

End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 201

Toxicity to daphnia and other :

aquatic invertebrates

(Chronic toxicity)

NOEC: 0,17 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: static test Test substance: WAF

Method: OECD Test Guideline 211

acetone:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.740 - 6.330

ma/l

Exposure time: 96 h Test Type: static test

LC50 (Pimephales promelas (fathead minnow)): 8.733 - 9.482

mg/l

Exposure time: 96 h

Test Type: flow-through test

Toxicity to algae/aquatic

plants

NOEC (Microcystis aeruginosa (blue-green algae)): 530 mg/l

Exposure time: 8 d Test Type: static test

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC: 2.112 mg/l Exposure time: 28 d

Species: Daphnia magna (Water flea)

Test Type: flow-through test

1-methoxy-2-propanol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

> Exposure time: 96 h Test Type: static test

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h Test Type: static test

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): >

1.000 mg/l

End point: Growth inhibition

Exposure time: 7 d Test Type: static test

# 12.2 Persistence and degradability

# **Components:**

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:

Biodegradability Inoculum: activated sludge

Biodegradation: 98 % Exposure time: 28 d

Method: OECD Test Guideline 301F

acetone:

Biodegradability Result: Readily biodegradable.

Biodegradation: 90,9 % Exposure time: 28 d

Method: OECD Test Guideline 301B

1-methoxy-2-propanol:

Result: Readily biodegradable. Biodegradability

Biodegradation: 96 % Exposure time: 28 d

Method: OECD Test Guideline 301E

# 12.3 Bioaccumulative potential

# **Components:**

acetone:

Partition coefficient: n-

octanol/water

: log Pow: -0,24

# Valvoline, Global

# **SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

# 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

# 12.6 Endocrine disrupting properties

**Product:** 

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

## 12.7 Other adverse effects

**Product:** 

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

# Global warming potential

Assessment Report of the Intergovernmental Panel on Climate Change (IPCC) of the United Nations Framework Convention on Climate Change (UNFCCC)

### **Components:**

#### carbon dioxide:

20-year global warming potential: 1
100-year global warming potential: 1
500-year global warming potential: 1
Radiative efficiency: 0,000013 Wm2ppb
Further information: Major Greenhouse Gases

# **SECTION 13: Disposal considerations**



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

Waste Code : The Waste code should be assigned in discussion between

the user and the waste disposal company.

The following Waste Codes are only suggestions:

16 05 04, gases in pressure containers (including halons)

containing hazardous substances

# **SECTION 14: Transport information**

# 14.1 UN number or ID number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

# 14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

(NAPHTHA (PETROLEUM), HYDROTREATED LIGHT)

IATA : Aerosols, flammable

# 14.3 Transport hazard class(es)

Class Subsidiary risks



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

ADN : 2 2.1
ADR : 2 2.1
RID : 2 2.1
IMDG : 2.1

2.1

### 14.4 Packing group

**ADN** 

IATA

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1

**ADR** 

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

**RID** 

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

**IMDG** 

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA\_P (Passenger)

Packing instruction : 203

(passenger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

# 14.5 Environmental hazards

**ADN** 

Environmentally hazardous : yes



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

**ADR** 

Environmentally hazardous ves

**RID** 

Environmentally hazardous ves

Marine pollutant yes

IATA (Passenger)

Environmentally hazardous ves

IATA (Cargo)

Environmentally hazardous yes

# 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

# 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be

considered: Number on list 75

If you intend to use this product as tattoo ink, please contact your

vendor.

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Not applicable

Regulation (EC) No 1005/2009 on substances that

Regulation (EU) 2019/1021 on persistent organic

Not applicable

deplete the ozone layer

Not applicable

pollutants (recast)

REACH - List of substances subject to authorisation Not applicable

# **SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

(Annex XIV) Regulation (EU) 2019/1148 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

acetone (ANNEX II)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P<sub>3</sub>b FLAMMABLE AEROSOLS

E2 **ENVIRONMENTAL HAZARDS** 

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including iet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points

Water hazard class (Germany)

TA Luft List (Germany)

: WGK 3 highly hazardous to water

5.2.1: Total dust: Not applicable

5.2.2: Inorganic substances in powdered form:

(a) to (d)

Not applicable

5.2.4: Inorganic substances in gaseous form:

Not applicable

5.2.5: Organic Substances:

Not applicable

5.2.7.1.1: Carcinogenic substance:

Not applicable

5.2.7.1.1: Quartz fine dust PM4:

Not applicable

5.2.7.1.1: Formaldehyde:

Not applicable 5.2.7.1.1: fibres:

# Valvoline<sub>™</sub> Global

### SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

Not applicable

5.2.7.1.2: Germ cell mutagens:

Not applicable

5.2.7.1.3: Substances toxic to reproduction:

Not applicable

5.2.7.2: Poorly degradable, easily enrichable and highly toxic

organic substances: Not applicable

# Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### The components of this product are reported in the following inventories:

TCSI : Not in compliance with the inventory

TSCA : Product contains substance(s) not listed on TSCA inventory.

AIIC : Not in compliance with the inventory

DSL : This product contains the following components that are not

on the Canadian DSL nor NDSL.

Proprietary of Valvoline Industrial Cleaner

ENCS : Not in compliance with the inventory

KECI : Not in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : Not in compliance with the inventory

NZIoC : Not in compliance with the inventory

# 15.2 Chemical safety assessment

No data available

#### **Inventories**

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

### SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

# **SECTION 16: Other information**

# **Full text of H-Statements**

H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.

H280 : Contains gas under pressure; may explode if heated.

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H319 : Causes serious eye irritation.

H336 : May cause drowsiness or dizziness.

H411 : Toxic to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

#### Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Press. Gas : Gases under pressure

Skin Irrit. : Skin irritation

STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

2006/15/EC : Europe. Indicative occupational exposure limit values

DE DFG BAT : Germany. MAK BAT Annex XIII
DE DFG MAK : Germany. MAK BAT Annex IIa

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

TRGS 903 : TRGS 903 - Biological limit values

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit 2006/15/EC / TWA : Limit Value - eight hours

DE DFG MAK / MAK : MAK value

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC

### SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024

International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk: IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan): ISO - International Organisation for Standardization: KECI - Korea Existing Chemicals Inventory: LC50 - Lethal Concentration to 50 % of a test population: LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quantitative) Structure Activity Relationship: REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

# **Further information**

Internal information: 000000274848

#### Classification of the mixture:

# Classification procedure:

| Aerosol 1         | H222, H229 | Calculation method |
|-------------------|------------|--------------------|
| Skin Irrit. 2     | H315       | Calculation method |
| Eye Irrit. 2      | H319       | Calculation method |
| STOT SE 3         | H336       | Calculation method |
| Aquatic Chronic 2 | H411       | Calculation method |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DE / EN



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Valvoline™ INDUSTRIAL CLEANER

Version: 4.0 Revision Date: 25.05.2024 Print Date: 27/11/2024