Printing date 02.10.2023

Version number 1.0



SECTION 1: Identification of the substance/mixture and of the company/ undertaking • 1.1 Product identifier

- · Trade name: COOLANT M3.0 CONCENTRATE
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- Application of the substance / the mixture Engine coolant Only for proper handling.
- \cdot 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

MOTOREX AG Bern–Zürich–Strasse 31, Postfach CH–4901 Langenthal Tel. +41 (0)62 919 75 75 www.motorex.com

· Further information obtainable from: msds@motorex.com

· 1.4 Emergency telephone number:

In case of a medical emergency following exposure to a chemical, the public should call NHS Direct in England or Wales 0845 46 47 or NHS 24 in Scotland 08454 24 24 24 (UK only).

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008
 Acute Tex. 4, H202 Harmful if awallowed

Acute Tox. 4 H302 Harmful if swallowed.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

· 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labelling:
- Ethane-1,2-diol

· Hazard statements

H302 Harmful if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure.

- · Precautionary statements
- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read carefully and follow all instructions.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

- P330 Rinse mouth.
- P314 Get medical advice/attention if you feel unwell.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Printing date 02.10.2023

Version number 1.0



(Contd. of page 1)

Trade name: COOLANT M3.0 CONCENTRATE

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

 Dangerous components: 		
CAS: 107-21-1 EINECS: 203-473-3 Reg.nr.: 01-2119456816-28	Ethane-1,2-diol STOT RE 2, H373; Acute Tox. 4, H302	≥70-≤100%
CAS: 84501-71-3 EINECS: 282-991-1	Potassium isononanoate Skin Irrit. 2, H315; Eye Irrit. 2, H319	1-3%
CAS: 29385-43-1 EINECS: 249-596-6 Reg.nr.: 01-2119979081-35	methyl-1H-benzotriazole Repr. 2, H361d; Aquatic Chronic 2, H411; Acute Tox. 4, H302	0.25-1%
Additional information: For the wording of the listed hazard phrases refer to section 16.		

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- 6.2 Environmental precautions: Dilute with plenty of water.
- Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 3)



(Contd. of page 2)

Printing date 02.10.2023

Version number 1.0

Trade name: COOLANT M3.0 CONCENTRATE

Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

· Information about fire - and explosion protection: Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.

· Further information about storage conditions:

The recommended storage temperature is (deg.C): ≤50°C

· Storage class: 10

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

107-21-1 Ethane-1,2-diol WEL Short-term value: 104** mg/m³, 40** ppm Long-term value: 10* 52** mg/m³, 20** ppm Sk *particulate **vapour

·DNELs				
107-21-1 Ethane-1,2-diol				
Dermal	DNEL / Workers / Systemic effects / Long-term		106 mg/kg/24h (worker)	
	DNEL/general population/Systemic effects/Lo	ong-term	53 mg/kg/24h (consumer)	
Inhalative	DNEL / Workers / Local Effects / Long-term		35 mg/m3 (worker)	
	DNEL/general population/Local effects/Long-	term	7 mg/m3 (consumer)	
29385-43-	1 methyl-1H-benzotriazole			
Oral	DNEL/general population/Systemic effects/Long-term		0.25 mg/kg/24h (consumer)	
	DNEL/general pop/Systemic effects/acute-short term		0.25 mg/kg/24h (consumer)	
Dermal	DNEL / Workers / Systemic effects / Long-term		0.5 mg/kg/24h (worker)	
	DNEL/general population/Systemic effects/Long-term		0.25 mg/kg/24h (consumer)	
Inhalative	DNEL / Workers / Systemic effects / Long-term		8.8 mg/m3 (worker)	
	DNEL/general population/Systemic effects/Long-term		4.4 mg/m3 (consumer)	
· PNECs				
107-21-1	Ethane-1,2-diol			
PNEC / Ad	PNEC / Aquatic organisms / Freshwater		10 mg/l (aquatic organisms)	
PNEC / Ad	PNEC / Aquatic organisms / Marine water		1 mg/l (aquatic organisms)	
PNEC/Aqu	PNEC/Aquatic org/intermittent releases(freshwater)		(aquatic organisms)	
PNEC/Aqu	PNEC/Aquatic organisms/Sewage treatment plant/STP		g/l (aquatic organisms)	
L			(Contd. on page 4)	



Printing date 02.10.2023

Version number 1.0

Trade name: COOLANT M3.0 CONCENTRATE

	(Contd. of page 3)
PNEC / Aquatic organisms / Sediment (freshwater)	37 mg/kg (aquatic organisms)
PNEC / Aquatic organisms / Sediment (marine water)	3.7 mg/kg (aquatic organisms)
PNEC / Terrestrial organism / Soil	1.53 mg/kg (terrestrial organisms)
29385-43-1 methyl-1H-benzotriazole	
PNEC / Aquatic organisms / Freshwater	0.008 mg/l (aquatic organisms)
PNEC / Aquatic organisms / Marine water	0.008 mg/l (aquatic organisms)
PNEC/Aquatic organisms/Sewage treatment plant/STP	39.4 mg/l (aquatic organisms)
PNEC / Aquatic organisms / Sediment (freshwater)	0.0025 mg/kg (aquatic organisms)
PNEC / Aquatic organisms / Sediment (marine water)	0.0025 mg/kg (aquatic organisms)
Additional informations. The lists we list during the mark	the second second second

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

• Appropriate engineering controls No further data; see section 7.

- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK. • Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



safety goggles

· Body protection: Protective work clothing

SECTION 9: Physical and	d chemical properties	
• 9.1 Information on basic phys • General Information	ical and chemical properties	
· Physical state	Fluid	
		(Contd. on page 5)



Printing date 02.10.2023

Version number 1.0

Trade name: COOLANT M3.0 CONCENTRATE	

	(Contd. of pag
Colour:	Pink
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and	
boiling range	170-185 °C (DIN EN ISO 3405)
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
	111 °C
Flash point:	-
Auto-ignition temperature:	398 °C (DIN 51794)
Decomposition temperature:	Not determined.
pH at 20 °C	7.5-9 (DIN 51369)
Viscosity:	
Kinematic viscosity	Not determined.
Consistency	
Dynamic:	Not determined.
Solubility	
water:	Fully miscible.
Partition coefficient n-octanol/water (log	,
value)	Not determined.
Heat Capacity	
Vapour pressure:	Not determined.
Density and/or relative density	Not determined.
Density at 20 °C:	1 119 a/am3 (ASTM D 4052)
	1.118 g/cm³ (ASTM D 4052) Not determined.
Relative density	
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of healt	th
and environment, and on safety.	
Explosive properties:	Product does not present an explosion hazard.
Solvent separation test:	
VOC (EC)	0.00 %
Change in condition	0.00 //
Evaporation rate	Not determined.
Evaporation rate	Not determined.
Information with regard to physical hazar	rd
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Calf reportive autotanese and ministeres	Void Void
Pyrophoric liquids	
Pyrophoric liquids Pyrophoric solids	Void
<i>Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures</i>	
Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit	Void
<i>Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures</i>	Void
Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water	Void Void
Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids	Void Void Void
Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water	Void Void Void Void

Г

Safety data sheet according to 1907/2006/EC, Article 31 Oil of Switzerlan Revision: 02.10.2023

Printing date 02.10.2023

Version number 1.0

Trade name: COOLANT M3.0 CONCENTRATE

		(Contd. of page 5)
· Corrosive to metals	Void	
 Desensitised explosives 	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Harmful if swallowed.

· LD/LC50 values relevant for classification:

LD/2000			
107-21-1	Ethane-1,2	-diol	
Oral	LD50	7,712 mg/kg (rat)	
	NOEL	150 mg/kg/24h (rat)	
	NOAEL	200 mg/kg/24h (rat)	
	NOAEL	12,500 ppm (mouse)	
Dermal	LD50	3,500 mg/kg (mouse)	
	NOAEL	2,200-4,400 mg/kg/24h (dog)	
Inhalative	LC50 / 6h	2.5 mg/l (rat)	
29385-43-1 methyl-1H-benzotriazole			
Oral	LD50	720 mg/kg (rat)	
	NOAEL	150 mg/kg/24h (rat)	
	LOAEL	6,700-11,700 mg/kg/24h (rat)	
Dermal	LD50	2,000 mg/kg (rabbit)	
• STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. • 11.2 Information on other hazards			
• Endocrine disrupting properties			
None of th	None of the ingredients is listed.		

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatio	· Aquatic toxicity:		
107-21-1 Ethane-1,2-diol			
LC50	7,286 mg/l/96h (fish)		
LC50	1,500 mg/l/28d (fish)		
EC50	3,536-13,000 mg/l/96h (algae / cyanobacteria)		
EC50	33,911 mg/l/21d (aquatic invertebrates)		
EC100	100 mg/l/48h (aquatic invertebrates)		
	(Contd. on page 7)		

GB



Printing date 02.10.2023

Version number 1.0

Trade name: COOLANT M3.0 CONCENTRATE

	(Contd. of page 6)
EC0	100 mg/l/48h (aquatic invertebrates)
EC50	100 mg/l/48h (aquatic invertebrates)
NOEC	7,500-15,000 mg/l/21d (aquatic invertebrates)
NOEC	100 mg/l/72h (algae / cyanobacteria)
NOEC	8,590-24,000 mg/l/7d (aquatic invertebrates)
	15,380-32,000 mg/l/7d (fish)
29385-	43-1 methyl-1H-benzotriazole
LOEC	37.6 mg/l/21d (aquatic invertebrates)
LC50	55-180 mg/l/96h (fish)
LC0	100 mg/l/96h (fish)
LC50	55 mg/l/48h (aquatic invertebrates)
	240 mg/l/48h (fish)
LC50	180 mg/l/72h (fish)
LC50	240 mg/l/24h (fish)
EC10	0.4-0.97 mg/l/21d (aquatic invertebrates)
EC10	4.17-8.56 mg/l/48h (aquatic invertebrates)
EC50	1,060 mg/l/24h (microorganisms)
EC10	1.18-10.5 mg/l/72h (algae / cyanobacteria)
EC50	29-75 mg/l/72h (algae / cyanobacteria)
EC50	18.4-37.6 mg/l/21d (aquatic invertebrates)
EC50	8.58-15.8 mg/l/48h (aquatic invertebrates)
NOEC	18.4 mg/l/21d (aquatic invertebrates)
NOEC	10-30 mg/l/72h (algae / cyanobacteria)
	30 mg/l/48h (aquatic invertebrates)
	ersistence and degradability No further relevant information available.
· 12.3 Bi	oaccumulative potential
107-21	-1 Ethane-1,2-diol
Partitio	n coefficient ≤1.36 [] (log Kow) (Bioaccumulation)
Biodegi	radability >90 % (28d) (Biodegradability) (OECD 301 A)
	obility in soil No further relevant information available.
	esults of PBT and vPvB assessment
· PBI: N	lot applicable. Not applicable.
	ndocrine disrupting properties
	oduct does not contain substances with endocrine disrupting properties.
	ther adverse effects
	onal ecological information:
	al notes: allow undiluted product or large quantities of it to reach ground water, water course or
	esvstem.

sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

(Contd. on page 8)

GB



Printing date 02.10.2023

Version number 1.0

Trade name: COOLANT M3.0 CONCENTRATE

(Contd. of page 7) Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.

· Uncleaned packaging:

- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR/RID/ADN, IMDG, IATA	Not classified as hazardous for transport
· 14.2 UN proper shipping name · ADR/RID/ADN, IMDG, IATA	Not classified as hazardous for transport
· 14.3 Transport hazard class(es)	
· ADR/RID/ADN, ADN, IMDG, IATA · Class	Not classified as hazardous for transport
· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	Not classified as hazardous for transport
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Not applicable.
 14.7 Maritime transport in bulk accord IMO instruments 	ing to Not applicable.
· UN "Model Regulation":	Not classified as hazardous for transport

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

· purity requirement

- Relevant phrases

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS: Abteilung Produktsicherheit

• Abbreviations and acronyms:

Acute Tox. 4: Acute toxicity – Category 4

(Contd. on page 9)

GB

Printing date 02.10.2023

Version number 1.0



Trade name: COOLANT M3.0 CONCENTRATE

(Contd. of page 8) Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eve Irrit. 2: Serious eve damage/eve irritation - Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Annex: Exposure scenario 1 · Short title of the exposure scenario Industrial use of coolants - Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites Product category PC4 Anti-Freeze and de-icing products PC16 Heat transfer fluids Process category PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC20 Use of functional fluids in small devices • Environmental release category ERC7 Use of functional fluid at industrial site · Description of the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Sheet. Conditions of use · Duration and frequency 5 workdays/week. · Physical parameters · Physical state Fluid · Concentration of the substance in the mixture The substance is main component. · Other operational conditions · Other operational conditions affecting environmental exposure No special measures required. · Other operational conditions affecting consumer exposure Not required. • Other operational conditions affecting consumer exposure during the use of the product Not applicable. · Risk management measures · Worker protection · Organisational protective measures No special measures required. · Technical protective measures No special measures required. · Personal protective measures No special measures required. · Measures for consumer protection No special measures required. · Environmental protection measures · Air No special measures required. · Water No special measures required. · Disposal measures Ensure that waste is collected and contained. · Disposal procedures Dispose of product residues with household waste. · Waste type Partially emptied and uncleaned packaging Exposure estimation · Consumer Not relevant for this Exposure Scenario. · Guidance for downstream users No further relevant information available. Annex: Exposure scenario 2

• Short title of the exposure scenario Professional use of coolants

Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

(Contd. on page 10)

GB ·

Page 10/11

Safety data sheet according to 1907/2006/EC, Article 31 Oil of Switzerlan Revision: 02.10.2023

Printing date 02.10.2023

Version number 1.0

Trade name: COOLANT M3.0 CONCENTRATE

	_
(Contd. of page 9)	
Product category PC4 Anti-Freeze and de-icing products	
PC4 Anti-Treeze and de-icing products PC16 Heat transfer fluids	
· Process category	
PROC1 Chemical production or refinery in closed process without likelihood of exposure or	
processes with equivalent containment conditions.	
PROC2 Chemical production or refinery in closed continuous process with occasional controlled	
exposure or processes with equivalent containment conditions	
PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities	
PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities	
PROC20 Use of functional fluids in small devices	
Environmental release category	
ERC9a Widespread use of functional fluid (indoor)	
ERC9b Widespread use of functional fluid (outdoor)	
Description of the activities / processes covered in the Exposure Scenario	
See section 1 of the annex to the Safety Data Sheet.	
Conditions of use	
Duration and frequency 5 workdays/week. Physical parameters	
· Physical state Fluid	
• Concentration of the substance in the mixture The substance is main component.	
· Other operational conditions	
• Other operational conditions affecting environmental exposure No special measures required.	
Other operational conditions affecting consumer exposure Not required.	
Other operational conditions affecting consumer exposure during the use of the product	
Not applicable.	
· Risk management measures	
· Worker protection	
Organisational protective measures No special measures required.	
Technical protective measures No special measures required.	
• Personal protective measures No special measures required.	
Measures for consumer protection No special measures required.	
Environmental protection measures Air No special measures required.	
• Water No special measures required.	
• Disposal measures Ensure that waste is collected and contained.	
• Disposal procedures Dispose of product residues with household waste.	
Waste type Partially emptied and uncleaned packaging	
Exposure estimation	
Consumer Not relevant for this Exposure Scenario.	
· Guidance for downstream users No further relevant information available.	
	_
Appart Expande acceptio 2	
Annex: Exposure scenario 3	
· Short title of the exposure scenario Private use of coolants	
• Sector of Use SU21 Consumer uses: Private households / general public / consumers	
Product category	
PC4 Anti-Freeze and de-icing products	
PC16 Heat transfer fluids	
• Process category	

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC20 Use of functional fluids in small devices

(Contd. on page 11)

⁻ GB

Page 11/11

Safety data sheet according to 1907/2006/EC, Article 31



Printing date 02.10.2023

Version number 1.0

Trade name: COOLANT M3.0 CONCENTRATE

(Contd. of page 10)	
Environmental release category	
ERC9a Widespread use of functional fluid (indoor)	
ERC9b Widespread use of functional fluid (outdoor)	
 Description of the activities / processes covered in the Exposure Scenario 	
See section 1 of the annex to the Safety Data Sheet.	
· Conditions of use	
 Duration and frequency 5 workdays/week. 	
· Physical parameters	
· Physical state Fluid	
 Concentration of the substance in the mixture The substance is main component. 	
· Other operational conditions	
 Other operational conditions affecting environmental exposure No special measures required. 	
 Other operational conditions affecting consumer exposure Not required. 	
 Other operational conditions affecting consumer exposure during the use of the product 	
Not applicable.	
· Risk management measures	
· Worker protection	
 Organisational protective measures No special measures required. 	
 Technical protective measures No special measures required. 	
Personal protective measures No special measures required.	
Measures for consumer protection No special measures required.	
Environmental protection measures	
Air No special measures required.	
Water No special measures required.	
Disposal measures Ensure that waste is collected and contained.	
 Disposal procedures Dispose of product residues with household waste. 	
Waste type Partially emptied and uncleaned packaging	
Exposure estimation	
Consumer Not relevant for this Exposure Scenario.	
· Guidance for downstream users No further relevant information available.	
GB	_